earch Sou	urces Analyt	tics M	y alerts	My list My setting	gs	
Quick Search	istern I. Dook to r	requilte 1	Search	of 10 Novt >		
Download PDF	Export	Print	E-mail	Create bibliography	Add to My List	Ci
Vehicle System Volume 43, Issu	Dynamics e 3, March 2005,	Pages 17	3-199			Thi (Sh
ISSN: 00423114 CODEN: VSDYA DOI: 10.1080/004 Document Type: . Source Type: Jou	l231105123313351 Article ırnal	11			View references (19)	Gha Dy mo (20
View at publishe	er Ifort of hig	h-spe	ed trains	s travelling ov	ver railway	You No gai sw
bridges	-	-		6	<u>.</u>	(20 Eng
bridges Kargarnovin, M.H ^a Mechanical E ^b Institute of So	. ^{a b}	n, D. ^{a b} , Th Irtment, S on Resea	hompson, D. ^{a b} harif Univers rch (ISVR), U	, Jones, C. ^{a b} 🛓 ity of Technology, Te niversity of Southam	hran, Iran oton, Southampton,	(20 Eng Vie
bridges Kargarnovin, M.H ^a Mechanical E ^b Institute of So United Kingdor Abstract	. ^{a b} M, Younesian ngineering Depa ound and Vibrati n	n, D. ^{a b} , Tł Irtment, S on Resea	nompson, D. ^{a b} harif Univers rch (ISVR), U	, Jones, C. ^{a b} ▲ sity of Technology, Te niversity of Southam	hran, Iran oton, Southampton,	(20 Eng Vie
bridges Kargarnovin, M.H ^a Mechanical E ^b Institute of So United Kingdor Abstract The ride paramet	. ^{a b} , Younesian ngineering Depa bund and Vibrati m comfort of high-s ric study is carried	n, D. ^{a b} , Th artment, S on Resea peed train d out using	hompson, D. ^{a b} harif Univers rch (ISVR), U s passing ove a time domai	, Jones, C. ^{a b} ity of Technology, Te niversity of Southamp r railway bridges is stud in model. The effects of	hran, Iran oton, Southampton, died in this paper. A f some design	(20 Eng Vie Info
bridges Kargarnovin, M.H ^a Mechanical E ^b Institute of So United Kingdor Abstract The ride paramet also ball indicator	. ^{a b} , Younesian ngineering Depa ound and Vibration comfort of high-s ric study is carried ers are investigate ast stiffness. The s, namely Sperlin	n, D. ^{a b} , Th artment, S on Resea peed train d out using ed such as influence g's comfor	harif Univers rch (ISVR), U s passing ove a time domais damping and of the track irre t index and th	, Jones, C. ^{a b}	hran, Iran oton, Southampton, died in this paper. A f some design nsion system and ed on two comfort on level are also	(20 Eng Vie Infe Ot
bridges Kargarnovin, M.H ^a Mechanical E ^b Institute of So United Kingdor Abstract The ride paramet also ball indicator studied. are cons layers of	. ^{a b} , Younesian ngineering Depa ound and Vibration comfort of high-s ric study is carried ers are investigate ast stiffness. The s, namely Sperlin Two types of railw idered. Timoshen	n, D. ^{a b} , Th artment, S on Resea peed train d out using ed such as influence g's comfor vay bridge ko beam f springs in	harif Univers rch (ISVR), U s passing ove g a time domais damping and of the track im t index and th s, a simple gir theory is used conjunction w	, Jones, C. ^{a b}	hran, Iran pton, Southampton, died in this paper. A f some design nsion system and ed on two comfort on level are also supported bridge nd bridge and two used to model the	(20 En Infe Of We
bridges Kargarnovin, M.H ^a Mechanical E ^b Institute of So United Kingdor Abstract The ride paramet also ball indicator studied. are cons layers of rail- pad characte	. ^{a b} , Younesian ngineering Depa bund and Vibrati n comfort of high-s ric study is carried ers are investigate ast stiffness. The s, namely Sperlin Two types of railw idered. Timoshen parallel damped s, sleepers and ba rized by its power of tracks. Nonlinea	n, D. ^{a b} , Tr irtment, S on Resea peed train d out using ed such as influence g's comfor vay bridge iko beam ti springs in allast. A ra r spectral o ar Hertz th	harif Univers rch (ISVR), U s passing ove g a time domai s damping and of the track irr t index and th s, a simple gir theory is used conjunction w indomly irregu density (PSD). ieory is used f eters in a carr	, Jones, C. ^{a b} ity of Technology, Te niversity of Southamp r railway bridges is stud in model. The effects of d stiffness of the susper egularity and train spec- te maximum acceleration rder and an elastically so for modelling the rail and ith a layer of mass are lar vertical track profile. The 'roughness' is ger for modelling the wheel- iane-track-bridge syste	hran, Iran pton, Southampton, died in this paper. A f some design nsion system and ed on two comfort on level are also supported bridge nd bridge and two used to model the is modelled, nerated for three -rail contact. The m such as the load	(20 Eng Vie Infe Of We Sh by
bridges Kargarnovin, M.H ^a Mechanical E ^b Institute of So United Kingdor Abstract The ride paramete also balla indicator studied. are cons layers of rail- pads characte classes of influence -stiffenin primary a Based of combina elasticall Group L	. ^{a b} , Younesian ngineering Depa ound and Vibrati m comfort of high-s ric study is carried ers are investigate ast stiffness. The s, namely Sperlin Two types of railw idered. Timoshen parallel damped s, sleepers and ba rized by its power of tracks. Nonlinea es of some nonline g characteristics of and secondary su n Galerkin's meth tion between the y supported bridg td.	n, D. ^{a b} , Th artment, S on Resea peed train d out using ed such as influence g's comfor vay bridge ko beam t springs in allast. A ra r spectral of ar Hertz th ear param of the rail- spension od of solur rigid and f jes but als	s passing ove a time domais s damping and of the track im- t index and th s, a simple gir theory is used conjunction w indomly irregu density (PSD). heory is used f eters in a carr pad and the ba systems, on th tion, a new an lexural mode s o other beam-	, Jones, C. ^{a b} ity of Technology, Te niversity of Southamp r railway bridges is stud in model. The effects of d stiffness of the susper egularity and train spee te maximum acceleration der and an elastically s for modelling the rail a vith a layer of mass are lar vertical track profile . The 'roughness' is ger for modelling the wheel- iage-track-bridge syste allast and that of rubben the comfort indicators are alytical approach is devision shapes, which could be type structures. © 200	hran, Iran oton, Southampton, died in this paper. A f some design nsion system and ed on two comfort on level are also supported bridge nd bridge and two used to model the is modelled, nerated for three -rail contact. The m, such as the load r elements in the re also studied. veloped for the used not only for 15 Taylor & Francis	(20 En) Vie Infe We Re Sh by Ka No tra (20 En)
bridges Kargarnovin, M.H ^a Mechanical E ^b Institute of So United Kingdor Abstract The ride paramet also ball indicator studied. are cons layers of rail- pads characte classes of influence -stiffenin primary a Based of combina elasticall Group Lt	.a b Younesian ngineering Depa ound and Vibration comfort of high-s ric study is carried ers are investigate ast stiffness. The s, namely Sperlin Two types of railwidered. Timoshen parallel damped s, sleepers and ba rized by its power of tracks. Nonlinea g characteristics of and secondary su n Galerkin's meth tion between the y supported bridg td.	n, D. ^{a b} , Th artment, S on Resea peed train d out using ed such as influence g's comfor vay bridge ko beam f springs in allast. A ra spectral of ar Hertz th ear param of the rail- spension od of solur rigid and f les but als ment	harif Univers rch (ISVR), U s passing ove g a time domai s damping and of the track irrr t index and th s, a simple gir theory is used conjunction w indomly irregu density (PSD). teory is used f eters in a carr pad and the bas systems, on th tion, a new an lexural mode s o other beam-	, Jones, C. ^{a b}	hran, Iran pton, Southampton, died in this paper. A f some design nsion system and ed on two comfort on level are also supported bridge nd bridge and two used to model the is modelled, nerated for three -rail contact. The m, such as the load r elements in the e also studied. veloped for the sused not only for 5 Taylor & Francis	(20 En Vie Inf O We Sh by Ka No (20 En VV0 St
bridges Kargarnovin, M.H ^a Mechanical E ^b Institute of So United Kingdor Abstract The ride paramet also ball indicator studied. are cons layers of rail- pads characte classes of influence -stiffenin primary a Based of Combina elasticall Group La	.a b Younesian ngineering Depa ound and Vibrati ound and Vibrati n comfort of high-s ric study is carried ers are investigate ast stiffness. The s, namely Sperlin Two types of railwidered. Timoshen parallel damped s, sleepers and ba rized by its power of tracks. Nonlinea g characteristics of and secondary su n Galerkin's meth tion between the y supported bridg td. original docum	n, D. ^{a b} , Th artment, S on Resea peed train d out using ed such as influence g's comfor vay bridge ko beam f springs in allast. A ra r spectral of ar Hertz th ear param of the rail- spension od of solur rigid and f les but als ment	harif Univers rch (ISVR), U s passing ove g a time domai s damping and of the track irrr t index and th s, a simple gir theory is used conjunction w indomly irregu density (PSD) leory is used f eters in a carr pad and the ba systems, on th tion, a new an lexural mode s o other beam-	, Jones, C. ^{a b}	hran, Iran pton, Southampton, died in this paper. A f some design nsion system and ed on two comfort on level are also supported bridge nd bridge and two used to model the is modelled, nerated for three -rail contact. The m, such as the load r elements in the e also studied. veloped for the used not only for 5 Taylor & Francis	(20 En Vie Inf O We Sh by Ka Sh by Ka C En Wu Sto Mu
bridges Kargarnovin, M.H ^a Mechanical E ^b Institute of So United Kingdor Abstract The ride paramete also ball indicator studied. are cons layers of rail- pads characte classes of influence -stiffenin primary a Based of combina elasticall Group Lt Language of English	.a b , Younesian ngineering Depa ound and Vibrati m comfort of high-s ric study is carried ers are investigate ast stiffness. The s, namely Sperlin Two types of railw idered. Timoshen parallel damped s, sleepers and ba rized by its power of tracks. Nonlinea es of some nonline g characteristics of and secondary su n Galerkin's meth tion between the y supported bridg td. original docum rds	n, D. ^{a b} , Th artment, S on Resea peed train d out using ed such as influence g's comfor vay bridge ko beam t springs in allast. A ra r spectral of ar Hertz th ear param of the rail- spension od of solur rigid and f les but als ment	s passing over a time domain s damping and of the track int t index and th s, a simple gir theory is used conjunction w indomly irregu density (PSD). teory is used f eters in a carr pad and the bas systems, on th tion, a new an lexural mode s o other beam-	, Jones, C. ^{a b}	hran, Iran pton, Southampton, died in this paper. A f some design nsion system and ed on two comfort on level are also supported bridge nd bridge and two used to model the is modelled, nerated for three -rail contact. The m, such as the load r elements in the e also studied. veloped for the e used not only for 5 Taylor & Francis	(2 Er Vi In O W R St by Ka St by Ka C Z (2 Er W St m (2 Vi

Engineering uncontrolled terms: Design parameters; High-speed trains; Power spectral density (PSD); Railway bridges Engineering main heading: Ground vehicles	A
References (19) View in table layout	My A
Export Print E-mail Create bibliography	Adc
 Select: Page Au, F.T.K., Wang, J.J., Cheung, Y.K. Impact study of cable-stayed railway bridges with random rail irregularities (2002) Engineering Structures 24 (5) pp. 529-541 Cited 23 times 	*
doi: 10.1016/S0141-0296(01)00119-5	
View at publisher	
 Berg, M. A model for rubber springs in the dynamic analysis of rail vehicles (2001) <i>J. Rail Rapid Transit</i>, 112, pp. 95-108. 	
 Dahlberg, T. Dynamic interaction between train and nonlinear railway model (2002) Proceedings of 5th International Conference on Structural Dynamics, pp. 1155-1160. Cited 6 times. Munich 	
4 (1995) EUROCODE 1: Basis of Design and Actions on Structures. Part 3: Traffic Loads on Bridges. Cited 7 times. ENV 1991-3	
 5 Esveld, C. (1989) Modern Railway Track. Cited 246 times. 	
 Fryba, L. (1996) Dynamics of Railway Bridges. Cited 113 times. (New York: Thomas Telford) 	
 Fryba, L. (1999) Vibration of Solids and Structures under Moving Loads. Cited 238 times. (Thomas Telford: New York) 	
8 Garg, V.K., Dukkipati, R.V. (1984) <i>Dynamics of Railway Vehicle Systems</i> . Cited 233 times. Canada: Academic Press	
 9 Geist, B., McLaughlin, J.R. Asymptotic Formulas for the Eigenvalues of the Timoshenko Beam (2001) Journal of Mathematical Analysis and Applications, 253 (2), pp. 341-380. Cited 18 times. doi: 10.1006/jmaa.2000.7125 	
View at publisher	
 Grandil, J., Ramondence, P. (1990) The Dynamic Behaviour of Railways on High-Speed Lines. Cited 2 times. SNCF: Paris 	

11	Kargarnovin, M.H., Younesian, D., Thompson, D.J., Jones, C.J.C. Nonlinear vibration and comfort analysis of high-speed trains moving over railway bridges (2004) <i>Proceedings of ESDA2004</i> Manchester
12 📄	Lin, Y., Xin, L., Yang, C., Zou, Z. Study on dynamic response of train excited by the irregularity of track on the high speed railway bridge (2001) <i>Journal of Vibration and Shock</i> , 20 (3), pp. 47-49+75+V. Cited 2 times.
13 📄	Yang, Y.B., Yau, J.D. A review of researches on vehicle- Bridge interaction with emphasis on high-speed rail bridges (1996) <i>Proceedings of 20th National Conference on Theoretical and Applied Mathematics</i> . Cited 3 times. Taipei
14 📺	Yang, Y.B., Wu, Y.S. Behavior of moving trains over bridges shaken by earthquakes (2002) <i>Proceedings of 5th International Conference on Structural Dynamics</i> , pp. 509-514. Cited 2 times. Munich
15 📄	Yang, Y.B., Lin, C.L., Yau, J.D., Chang, D.W. Mechanism of resonance and cancellation for train-induced vibrations on bridges with elastic bearings (2004) <i>Journal of Sound and Vibration</i> , 269 (1-2), pp. 345-360. Cited 13 times. doi: 10.1016/S0022-460X(03)00123-8
16 📄	Yau, J.D., Yang, Y.B., Kuo, S.R. Impact response of high- Speed rail bridges and riding comfort of rail cars (1999) <i>Engineering Structures</i> , 25, pp. 251-265. Cited 2 times.
17 📄	Yau, JD., Wu, YS., Yang, YB. Impact response of bridges with elastic bearings to moving loads (2001) <i>Journal of Sound and Vibration</i> , 248 (1), pp. 9-30. Cited 23 times. doi: 10.1006/jsvi.2001.3688
18 📄	View at publisher Wu, YS., Yang, YB. Steady-state response and riding comfort of trains moving over a series of simply supported bridges (2003) <i>Engineering Structures</i> , 25 (2), pp. 251-265. Cited 23 times. doi: 10.1016/S0141-0296(02)00147-5
19 📄	View at publisher Wu, T.X., Thompson, D.J. The effects of track non-linearity on wheel/rail impact (2004) <i>Proceedings of the Institution of Mechanical Engineers, Part F: Journal of Rail and Rapid</i> <i>Transit</i> , 218 (1), pp. 1-16. Cited 12 times.

Kargarnovin, M.H.; Mechanical Engineering Department, Sharif University of Technology, Tehran, Iran Copyright 2008 Elsevier B.V., All rights reserved.										
Vehicle System Dynamics Volume 43, Issue 3, March 2005, Pages 173-199										
View search history B	ack to results	< Previous	37 of 40 Ne	ext >						
earch Sources	Analytics	My alerts	My list	My settings						
About Scopus		Contact an	d Support		About Elsevier					
About Scopus What is Scopus Content coverage		Contact and Contact and Live Chat	d Support d support		About Elsevier About Elsevier About SciVerse					
About Scopus What is Scopus Content coverage What do users think		Contact and Contact and Live Chat	d Support d support		About Elsevier About Elsevier About SciVerse About SciVal					
About Scopus What is Scopus Content coverage What do users think Latest Tutorials		Contact and Contact and Live Chat	d Support I support		About Elsevier About Elsevier About SciVerse About SciVal Terms and Conditions Privacy Policy					